

Technical questionnaire by Fey Lamellenringe GmbH Fax: +49 (0) 8231 9618 - 96 · Phone: +49 (0) 8231 9618 - 0

© Copyright by Fey Lamellenringe

Company address				
Pe	rson in charge			Department
Phone				Fax
E-mail				Date
Machine type				Project No.
-	The laminar rings must seal agains			
	☐ Splash water entry	☐ Severe contamination		☐ Cooling lubricant entry ☐ Dust entry
	☐ Oil leakage	☐ Grease leakage	:	☐ Other media:
-	Protect other seals	☐ yes / which	□ no	
-	Operating temperature	(in ring area °C)		
-	Housing speed	(RPM / rotational o	direction)	
-	Shaft speed	(RPM / rotational o	direction)	
-	Axial movement	☐ yes/in mm	□ no	
-	Radial movement	☐ yes/in mm	□ no	
-	Angular movement	☐ yes/in°	□ no	
-	Operating pressure (Medium)	☐ yes / in bar	□ no	
-	Re-greasing option	u yes / which	□ no	
-	Stainless steel laminar rings	☐ yes	□ no	
-	Housing materials (hardened)	u yes / hardness	□ no	
-	Shaft material (hardened)	u yes / hardness	□ no	
-	New design	☐ yes	□ no	
-	Changeover to laminar rings	☐ yes	□ no	
-	Which type of sealing was used before?			
-	Permissible leakage			
-	Lifespan			
-	What would the demand be:	☐ one time (pied	ces/set)	
		☐ monthly (pied	ces/set)	
		☐ annually (pied	ces/set)	
Additional questions for the use of Fey retainer rings:				
-	Will the retaining rings be axially loaded (against)			
-	How large is the axial load against the rings (in N)			
-	Will the disassembly notches be re	equired?		

Pages 40-41